

sgg 4mm **Mistlite**

4mm **Mistlite** 4mm Mistlite eu

:

- 1. : /
- 2. : 3.2 mm ± 0.2 mm;4mm ± 0.2 mm
- 3. : 91.6%
- 4. : 90.7%
- 5. : Mistlite ()1
- 6. : 2140x3300mm

:



| | |
|--|--|
| Description | Ultra Clear/ Low Iron Patterned Glass |
| Content of Iron | $\leq 0.02\% \text{ Fe}^{2+}\text{O}^{3+}$ |
| Thickness | 3.2mm $\pm 0.2\text{mm}$; 4mm $\pm 0.2\text{mm}$ |
| Light Transmission (Procedure EN410) | TL 91.6 $\pm 0.5\%$ at 3.2mm TL 91.5 $\pm 0.5\%$ at 4mm |
| Energetic transmission Measured on Polished glass (DIN ISO 9050) | TE 90.7 $\pm 0.5\%$ at 3.2mm TE 90.2 $\pm 0.5\%$ at 4mm |
| Surface | Mistlite (Textured), structured on one side |
| Tolerance of dimensions | $\pm 2\text{mm}$ |
| Squareness (DIN 1249/pr EN12150) | Max difference 2mm |
| Bow | Max. 3mm/m |
| Needle Bubbles | Diameter $< 0.5\text{mm}$ allowed |
| Quality | Inclusions |
| Criteria from prEN572-5/94: (Distance of observation 1,5m perpendicular to glass sheet parallel to a grey background at a distance of 3m at diffuse day light) | All optical detectable inclusions are not permitted. |
| Round bubbles | Diameter $< 2\text{mm}$ allowed. Diameter $> 2\text{mm}$ not allowed. |
| Stretched bubbles | Width $> 0,8\text{mm}$ not allowed For a width $< 0,8\text{mm}$: Length smaller 1mm, allowed Length between 1mm and 3mm, 4 pieces per sheet; Length between 3mm and 5mm, 1 pieces per sheet; Length bigger 5mm, not allowed |
| Open bubbles | Independent of size not allowed |

11

□□□□□□ a□□□□□□temperable □□□□□□eu □□□□□□

| | | | | | | | | |
|--|--|--|--|--|--|--|--|---|
| | | | | | | | | : |
| | | | | | | | | : |

[illegible]



4 mm กระจก Mislite กระจกใส:

กระจก



□□□□□□



□□□□:

