SZG 21.52mm laminated glass with bottom silk screen print- best building glass manufacturers and factory in China

21.52mm laminated silk screen print glass is a kind of laminated glass, which is made of one layer of **10mm silk screen glass** and one layer of 10mm tempered glass sandwish together. The middle layer is 1.52mm PVB film, after heating and high-pressure special process, the two layers of glass adhesion together. With the process of lamination, the glass is super strong and high protective against breakage. It’s a kind of safety glass for modern building construction.

Laminated tempered glass features:

1.Tempered glass characteristic: screen printing laminated glass has tempered glass features, that is, after breakage, will break into small granular after breakage, will not harm human beings.

2. Safety glass features: Due to PVB have strong bondness, laminated glass breakage will not fall down and bond by pvb film and .

3. Sound resistance function: The density of film are different with glass so the laminated glass can stop sound transmission at some level.

4. UV rays resistance: Silk screen laminated glass reduces the penetration of UV rays and protect indoor objects from UV rays radiation.



Specification:

Glass thickness :21.52mm laminated silk screen glass

Other glass thickness: 9.52mm ceramic frit laminated glass, 11.52mm ceramic frit laminated glass, 13.52mm ceramic frit laminated glass, 17.52mm ceramic frit laminated glass, 25.52mm ceramic frit laminated glass, 31.52mm ceramic frit laminated glass, 39.52mm ceramic frit laminated glass etc

Max size: 3300x12000mm

Glass thickness: 4mm+4mm silk screen glass,5mm+5mm silk screen glass,6mm+6mm silk screen glass,8mm+8mm silk screen glass,10mm+10mm silk screen glass, 12mm+12mm silk screen glass etc

Glass color: transparent laminated glass,low iron laminated glass,green laminated glass,bronze laminated glass,blue laminated glass,gray laminated glass,obscure laminated glass,Frit printed laminated glass etc.

PVB thickness: 0.76mm laminated glass,1.14mm laminated glass,1.52mm laminated glass,1.9mm laminated glass etc



Applications:

21.52mm silk screen laminated glass have wide usage in modern construction, Mostly in following areas:

1. Glass railings, glass balustrade, glass fence etc.

2.Glass partition, glass partition wall, glass wall

3.Glass facade, glass curtain wall etc

Quality Certificates:

21.52mm laminated glass with bottom silk screen printing are produced strictly under ISO9001 Quality System and have passed following domestic and international quality standards:

1. 21.52mm laminated glass with bottom silk screen printing meet CCC(Chinese Safety Glass Compulsory Certification)

2. 21.52mm laminated glass with bottom silk screen printing meet China laminated glass standard GB9962.

3. 21.52mm laminated glass with bottom silk screen printing meet meet European safety glass standard EN14449:2005.

4. 21.52mm laminated glass with bottom silk screen printing meet American safety glass standard SGCC ANSI Z97.

Verification of Conformity

Glass in building - Laminated glass and laminated safety glass - Evaluation of conformity / Product standard
EN 14449:2005

QUALITY MANAGEMENT SYSTEM

CERTIFICATE

Shenzhen Sun Global Glass Co., Ltd

ISO 9001:2015

DECLARATION OF CONFORMITY

EC Declaration of CPD Conformity

SGS

TEST REPORT

SGS

TEST REPORT

SGS

TEST REPORT

DECLARATION OF CONFORMITY

EC Declaration of CPD Conformity

SGS

TEST REPORT

SentryGlas

Certificate No. DPSGP14006

DuPont Glass Laminating Solutions

is pleased to confirm that the company:

SHENZHEN SUN GLOBAL GLASS CO., Ltd

has successfully passed the qualification process of SentryGlas® on May, 2014.

This certificate is valid until the date shown in the below table as long as your manufacturing process for laminated safety glass remains unchanged. Renewal is subject to validation of newly supplied laminates.

Date: 2014-05-29

By DuPont:

Validity: